

Posicionador Actuador Super Jack

Características:

Posicionador

Input Voltage	110 VAC 60 Hz or 220 VAC 50 Hz (choose at time of purchase) 13/18 VDC (F Type via Coaxial Cable)
Output Voltage	13/18 VDC (F Type / According to input) 36 VDC vía motor cable>
Maximum Current	2.2A
Power Consumption	Standby: 5W Maximum: 70W>
Position Memories	99 / 8 / 4
Protocol	DiSEqC 1.2/1.0
Remote Control	IR
Operating Temperature	5C to 40C (41F to 104F)
Storage Temperature	-20C to 60C (-4F to 140F)
Dimensions (WxHxD)	225x160x75mm (Net) 275x205x83mm (Gross)
Weight	1.6 Kg (Net) 1.7 Kg (Gross)

Actuador

- Superior de Lucha contra el óxido proceso.
- Tubo de alimentación de acero recubierto y de hardware de alto grado plateed.
- Excelente prueba de agua.
- Proporcionar 2 ofertas y los agujeros de drenaje 3.
- Súper sensor de lectura.
- Rutenio Contactos de chapado asegura una mayor vida del sensor.
- Herméticamente sellados en un ambiente limpio para eliminar los efectos nocivos del polvo, la corrosión oxidación.
- El diseño avanzado permite ninguna oportunidad para que se pegue, vinculante o uso de juntas con bisagras.
- Plástico impregnado para la instalación libre de riesgos y fáciles de reemplazar.

Rating Load@25V	440lbs
Maximum load@25v	795lbs
Power Supply Voltage	DC24-36
REED Sensor Currency	?=10mA