

SDS-16 BLONDER TONGUE

\$3,800.00



Divisor de 16 vías con un rango de 5-1000 MHz sellado con soldadura.

SDS-16 BLONDER TONGUE

Características:

Features & Benefits

- Zinc Die-cast Housing with Corrosion Protection
- Solde Back
- -120 dB RFI

Specifications

	SDS-12	SDS-16
Loss (dB)		
5 - 40 MHz:	11	14
40 - 400 MHz:	11	14
400 - 500 MHz:	11.5	14.5
500 - 600 MHz:	12	15.5
600 - 1000 MHz:	13	15.5
Isolation (dB)		
5 - 40 MHz:	28	23
40 - 400 MHz:	32	28
400 - 500 MHz:	30	25
500 - 600 MHz:	28	22
600 - 1000 MHz:	25	22
Return Loss Input (dB)		
5 - 40 MHz:	18	18
40 - 400 MHz:	18	18
400 - 500 MHz:	18	18
500 - 600 MHz:	18	18
600 - 1000 MHz:	18	18
Return Loss Output (dB)		
5 - 40 MHz:	18	18
40 - 400 MHz:	20	22
400 - 500 MHz:	20	22

500 - 600 MHz:	20	20
600 - 1000 MHz:	18	18

Ordering Information

Model	Stock No.	Description
SDS-12	1938	Splitter, 12 Way Solder Back, 5-1000 MHz
SDS-16	1939	Splitter, 16 Way Solder Back, 5-1000 MHz