



MULTITAP DMT-1000-4

Características:

- ? 1 GHz Pasivo BLONDER TONGUE
- ? Los modelos DMT-2, de 4 y 8 puertos tienen conectores F de latón enchapado
- ? Blindaje RFI de 120 dB
- ? Carcasa fundida a presión

DMT-1000-4	8	11	14	17	20	23	26	29	32	35
Tap Value										
Insertion Loss (dB)										
@5-10 MHz:	*	3.2	1.8	1.3	1.0	0.8	0.8	0.8	0.8	0.8
@10-450 MHz:	*	3.5	1.8	1.4	1.2	0.8	0.8	0.8	0.8	0.8
@450-550 MHz:	*	4.0	2.3	1.6	1.4	1.2	1.0	1.0	1.0	1.0
@550-750 MHz:	*	4.4	3.0	1.8	1.6	1.4	1.2	1.2	1.2	1.2
@750-1000 MHz:	*	4.8	3.7	2.2	2.0	1.8	1.5	1.5	1.5	1.5
Out to Tap Isolation (dB)										
@5-10 MHz:	-	22	22	25	30	30	30	32	32	33
@10-450 MHz:	-	26	27	30	36	36	38	40	42	44
@450-550 MHz:	-	24	28	30	35	35	35	40	42	42
@550-750 MHz:	-	23	24	27	32	32	34	35	38	40
@750-1000 MHz:	-	23	24	27	32	32	34	35	38	40