



MULTITAP DMT-1000-8

Características:

- ? 1 GHz Pasivo BLONDER TONGUE
- ? Los modelos DMT-2, de 4 y 8 puertos tienen conectores F de latón enchapado
- ? Blindaje RFI de 120 dB
- ? Carcasa fundida a presión

DMT-1000-8	11	14	17	20	23	26	29	32	35
Tap Value									
Insertion Loss (dB)									
@5-10 MHz:	*	3.6	1.8	1.4	1.0	1.0	1.0	1.0	1.0
@10-450 MHz:	*	4.2	2.2	1.6	1.1	1.1	1.1	1.1	1.1
@450-550 MHz:	*	4.5	2.5	2.0	1.5	1.2	1.2	1.2	1.2
@550-750 MHz:	*	4.6	3.0	2.2	1.8	1.3	1.3	1.3	1.3
@750-1000 MHz:	*	4.9	3.2	2.6	2.2	1.5	1.5	1.5	1.5
Out to Tap Isolation (dB)									
@5-10 MHz:	-	23	24	27	28	30	32	34	36
@10-450 MHz:	-	24	25	28	30	32	34	35	38
@450-550 MHz:	-	27	27	30	34	38	40	42	42
@550-750 MHz:	-	25	27	30	33	33	35	38	40
@750-1000 MHz:	-	25	27	30	33	33	35	38	40