

Modulador Ágil Análogo

Características:

INTRODUCTION

The SK-4000M is a commercial grade, SAW filtered, and frequency agile modulator. Setup andtuningareeasy and straightforward taking advantage of the front panel access to all level controls and indicators. The SK-4000M agile modulator provides system operators the engineering ease and flexibility associated with new headend deployments, upgrades and system maintenance.

FEATURES

- 1. SAW filtered for maintenance free adjacent channel configuration
- 2. 55dBmV RF output level
- 3. Phase lock loop frequency control
- 4. None-volatile memory maintains channel selection in event of power loss
- 5. Three-digit blue LED display and controls for convenient monitoring and operation
- 6. Switching power supply for installation flexibility and precise voltage regulation
- 7. Available in NTSC or PAL BG/DK configurations

SPECIFICATIONS

	OUTPUT	
RF	Output Frequency	45~860MHz any channel
	Output Connector	F Connector
	Output Level	115 dBμV(Adj.)
	Test Point	-20 dB ±3dB
	A / V Ratio	-11 ~ -18 dB(Adj.)
	Frequency Stability	±10KHz
	Output Impedance	75 Ohms
	INPUT	•
VIDEO	Video Input Level	0.6-1.5 Vp-p (87.5% Modulation)
	Input Connector	Yellow RCA Jack
	Video C/N	60dB
AUDIO	Input Level	0.8Vp-p (25KHz Peak Deviation)
	Input Connector	White RCA Jack
	GENERAL	
POWER AND SIZE	Voltage	AC 110 ~ 220V
	Power Consumption	10 W
	Dimensión	19" x 1.75" x 6.6"