

Receptor Topfield SRP-2110 HD-PVR

Características:

Tunner & Channel Decoder			
2 Tuners	DVB-S, DVB-S2	DiSEqC Control	Version 1.0/1.1/1.2/1.3 Compatible
Input / Loop through Connector	F-type, IEC 169-24, Female	Demodulation	QPSK,8PSK
Frequency Range	950 ~ 2150 MHz	Input Symbol Rate	2~45MSPS(DVB-S2 QPSK), 10~30MSPS(DVB-S2 QPSK/8PSK)
LNB Power & Polarización	Vertical: +13.5 VDC Horizontal: +18 VDC Current: Max. 500mA with Overload Protection	Code Rate	QPSK: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
22KHz Tone	Frequency: 22 ± 1KHz Amplitude: 0.65 ± 0.2V		

MPEG Transport Stream A/V Decoding	
Transport Stream	MPEG-2, H.264 Transport stream Specification
Profile Level	HP or MP@HL or ML
Aspect Ratio	4:3, 16:9, Pan & scan, Letterbox
Video Resolution	576i, 576p, 720p, 1080i
Audio Decoding	MPEG-1 Layer 1,2 and 3, WMA, AAC & Dolby Downmix

Main System	
CPU	BCM7400
Memory	Flash-ROM: 32MB System RAM:512MB DDR2, Video RAM:256MB DDR2
HDD	EEPROM: 16Kbit 500GB

Conditional Access Interface	
PCMCIA	2 slots
	DVB Common Interface Standard

Physical Specification	
Size(W x H x D)	340 x 258 x 82 mm
Weight (Net)	3.8 Kg

A/V & Data In / Out			
TV-Scart	Video CVBS/S-VIDEO/RGB Output Audio L/R output	SPDIF, Coaxial	Digital audio or Dolby bitstream output
VCR-Scart	Video CVBS output Audio L/R output Video CVBS/RGB/S-Video input for bypass Audio L/R output	USB	USB 2.0,3Port (Front:2Port, Rear: 1Port)
		LAN	RJ45, 10/00 Base-T PHY
Component	YPbPr 480i/576i, 480p/576p, 720p, 1080i Output	SATA	External SATA 2.0
RCA A/V	Video CVBS output Audio L/R output	HDMI	HD A/V Output, 480i/576i,480p/576p,720p,1080i Output

Front Pannel	
Keys	6 Keys (CH-/+,VOL-/+,Menu: Touch Interface)
VFD	Service info. or Time display
RCU	55 Keys
USB	USB 2.0, 2Port

Power Supply	
Input Voltage	90-250VAC, 50/60 Hz
Type	SMPS
Power Consumption	Running: Max. 67W, Standby: 7W
Protection	Separate internal fuse The input shall have lightning protection