

RECEPTOR TOPFIELD SRP-2110 HD-PVR
\$13,950.00


Único Receptor Digital multimedia de alto rendimiento, Solución TOTAL con Grabadora-HD-Picture & Picture-USB

Receptor Topfield SRP-2110 HD-PVR
Características:

Tuner & Channel Decoder			
2 Tuners	DVB-S, DVB-S2	DiSEqC Control	Version 1.0/1.1/1.2/1.3 Compatible
Input / Loop through Connector	F-type, IEC 169-24, Female	Demodulation	QPSK, 8PSK
Frequency Range	950 - 2150 MHz	Input Symbol Rate	2-45MSPS(DVB-S2 QPSK), 10-30MSPS(DVB-S2 QPSK/8PSK)
LNB Power & Polarización	Vertical: +13.5 VDC Horizontal: +18 VDC Current: Max. 500mA with Overload Protection	Code Rate	QPSK: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
22KHz Tone	Frequency: 22 ± 1KHz Amplitude: 0.65 ± 0.2V		

MPEG Transport Stream A/V Decoding		Main System	
Transport Stream	MPEG-2, H.264 Transport stream Specification	CPU	BCM7400
Profile Level	HP or MP@HL or ML	Memory	Flash-ROM: 32MB System RAM: 512MB DDR2, Video RAM: 256MB DDR2
Aspect Ratio	4:3, 16:9, Pan & scan, Letterbox	HDD	EEPROM: 16Kbit 500GB
Video Resolution	576i, 576p, 720p, 1080i		
Audio Decoding	MPEG-1 Layer 1, 2 and 3, WMA, AAC & Dolby Downmix		

Conditional Access Interface		Physical Specification	
PCMCIA	2 slots	Size(W x H x D)	340 x 258 x 82 mm
	DVB Common Interface Standard	Weight (Net)	3.8 Kg




A/V & Data In / Out			
TV-Scart	Video CVBS/S-VIDEO/RGB Output Audio L/R output	SPDIF, Coaxial	Digital audio or Dolby bitstream output
VCR-Scart	Video CVBS output Audio L/R output Video CVBS/RGB/S-Video input for bypass Audio L/R output	USB	USB 2.0, 3Port (Front: 2Port, Rear: 1Port)
Component	YPbPr 480i/576i, 480p/576p, 720p, 1080i Output	LAN	RJ45, 10/00 Base-T PHY
RCA A/V	Video CVBS output Audio L/R output	SATA	External SATA 2.0
		HDMI	HD A/V Output, 480i/576i, 480p/576p, 720p, 1080i Output

Front Panel		Power Supply	
Keys	6 Keys (CH-/, VOL-/, Menu: Touch Interface)	Input Voltage	90-250VAC, 50/60 Hz
VFD	Service info. or Time display	Type	SMPS
RCU	55 Keys	Power Consumption	Running: Max. 67W, Standby: 7W
USB	USB 2.0, 2Port	Protection	Separate internal fuse The input shall have lightning protection



 **Antenas de México**

LOS EXPERTOS EN INSTALACIONES
VÍA SATÉLITE DESDE 1980

 744 4 45 67 39 |  744 4 45 73 59 |  744 3 54 66 05

www.parabolicas.mx