

AMPLIFICADOR CDA-1P TRU SPEC

\$3,800.00



Amplificador bi-direccional 15dB pasivo para sistemas de banda ancha.

Amplificador CDA-1P TRU SPEC

Características:

Total # of Channels	Input Level (dBmV)	Output Level (dBmV)
7	40dBmV	55dBmV
12	38dBmV	53dBmV
36	28dBmV	43dBmV
48	24dBmV	39dBmV
78	19dBmV	34dBmV
108	14dBmV	29dBmV
125	10dBmV	25dBmV
158	8dBmV	23dBmV
Bandwidth		5~1000MHz
Gain (FWD) 54~1000MHz		
CDA-1 Series	15dB	
CDA-2 Series	11dB	
CDA-4 Series	8dB	
Outputs		
CDA-1	1	
CDA-2	2	
CDA-4	4	
Maximum Output (158 channels)		
CDA-1	23dBmV	
CDA-2	19dBmV	
CDA-4	15dBmV	
Gain (REV) 5~42 MHz		
CDA-1	10dB (1A) / -1dB(1P)	
CDA-2	7dB (2A) / -4.5dB (2P)	
CDA-4	4dB (4A) /-7.5dB (4P)	
Flatness	0.75dB	
Noise Figure (FWD)	3dB	
Composite Second Order (FWD)	62dB	
Composite Triple Beat (FWD)	74dB	
Power Input	12VDC	
Power Required	2.5Watt	
Dimensions	3.4" (L) x 2.4" (D) x 0.9" (H)	
Weight	0.8 lbs	