

AMPLIFICADOR CA-30/1000 PICO MACOM
\$ 15,950.00


Distribuidor Amplificador 1 GHz de banda ancha push-pull.

Amplificador CA-30/1000 Pico Digital
Características:

| CA-30/1000 Specifications | | |
|----------------------------------|-------------------------------|---------------------|
| Bandwidth | 54 MHz to 1000 MHz | |
| Gain (FWD) 54 to 1000 MHz | 30 dB | |
| Max. Output (158 ch.) | 40 dBmV | |
| Flatness | 0.5 dB | |
| Noise Figure (FWD) | 5 dB | |
| Composite Second Order (FWD) | 70 dB | |
| Composite Triple Beat (FWD) | 61 dB | |
| Input Test Point Loss | 20 dB | |
| Power Input | DC 24V 1A | |
| Power Required | 4 Watts | |
| Dimensions | 8" (L) x 2.75" (D) x 4.5" (H) | |
| Weight | 2.3 lbs. | |
| CA-30/1000 | | |
| Total # of Channels | Input Level(dBmV) | Output Level (dBmV) |
| 12 | 23 | 53 |
| 24 | 20 | 50 |
| 36 | 19 | 49 |
| 48 | 17 | 47 |
| 72 | 16 | 46 |
| 96 | 14 | 44 |
| 144 | 13 | 43 |
| 158 | 12 | 42 |